


## Horizontal model 3MU 30-10000 VA



### Features

Voltages: Max. 1000 V  
 Power: 30...10000 VA  
 Frequency: 50/60 Hz, other frequencies on request  
 IP-class: IP20  
 Operating temperature range: -30...+40°C  
 Thermal classes: B (130°C), F (155°C), H (180°C)  
 Standards: IEC 61558-2

S [VA]	Core	A [mm]	B [mm]	C [mm]	D [mm]	H [mm]	Ø [mm]	m [kg]
30	3UI 48/17	96	106	50	94	54	4,2x6	0,9
45	3UI 48/26	96	106	50	94	54	4,2x6	1,3
63	3UI 60/21	120	130	78	117	63	5,8x7	1,8
100	3UI 60/31	120	130	78	117	63	5,8x7	2,4
200	3UI 75/26	150	163	80	145	73	5x10	3,5
350	3UI 75/41	150	163	80	145	88	5x10	5,2
450	3UI 90/31	179	192	133	174	88	7x13	6,5
750	3UI 90/51	179	192	133	174	108	7x13	9,0
1000	3UI 114/40	230	236	173	212	90	8,5x18	16,0
1600	3UI 114/64	230	236	173	212	114	8,5x18	20,0
2000	3UI 114/64	230	236	173	212	114	8,5x18	20,5
2500	3UI132/46	265	276	190	248	130	8,5x18	22,0
3000	3UI 132/72	265	276	190	248	156	8,5x18	31,0
4000	3UI 150/52	300	307	220	277	115	8,5x18	31,5
4500	3UI 150/65	300	307	220	277	128	8,5x18	36,0
5000	3UI 150/77	300	307	220	277	140	8,5x18	42,0
6000	3UI 150/92	300	307	220	277	155	8,5x18	49,0
6300	3UI180/63	360	300	340	240	170	10x18	50,0
8000	3UI 180/63	360	300	340	240	170	10x18	50,0
9000	3UI 180/78	360	300	340	240	185	10x18	60,0
10000	3UI 180/92	360	300	340	240	199	10x18	70,0

