

Vertical model with enclosure 3PUK 1-100 kVA



Features

Voltages:	Max. 1000 V
Power:	1-100 kVA
Frequency:	50/60 Hz, other frequencies on request
IP-class	IP23, IP33 or IP44*
Operating temperature range:	-30...+40°C
Standards:	IEC 61558-2, IEC 60076

* bigger core size than with IP23-enclosure

S [kVA]	Core	Enclosure	A [mm]	B [mm]	C [mm]	D [mm]	H [mm]	Ø [mm]
1,0	3UI 114/40	3PUK23 114-150	380	412	340	173	392	12x18
1,6	3UI 114/64	3PUK23 114-150	380	412	340	173	392	12x18
2,0	3UI 114/64	3PUK23 114-150	380	412	340	173	392	12x18
2,5	3UI 132/46	3PUK23 114-150	380	412	340	190	392	12x18
3,0	3UI 132/72	3PUK23 114-150	380	412	340	190	392	12x18
4,0	3UI 150/52	3PUK23 114-150	380	412	340	220	392	12x18
4,5	3UI 150/65	3PUK23 114-150	380	412	340	220	392	12x18
5,0	3UI 150/77	3PUK23 114-150	380	412	340	220	392	12x18
6,0	3UI 150/92	3PUK23 114-150	380	412	340	220	392	12x18
6,3	3UI 180/63	3PUK23 180-210	440	535	400	264	522	12x18
8,0	3UI 180/78	3PUK23 180-210	440	535	400	264	522	12x18
10,0	3UI 180/78	3PUK23 180-210	440	535	400	264	522	12x18
12,5	3UI 210/73	3PUK23 180-210	440	535	400	316	522	12x18
16,0	3UI 210/73	3PUK23 180-210	440	535	400	316	522	12x18
20,0	3UI 210/103	3PUK23 180-210	440	535	400	316	522	12x18
25,0	3UI 240/83	3PUK23 240-270	490	709	450	356	682	12x18
31,5	3UI 240/110	3PUK23 240-270	490	709	450	356	682	12x18
40,0	3UI 270/120	3PUK23 240-270	490	709	450	350	682	12x18
50,0	3UI 270/150	3PUK23 240-270	490	709	450	350	682	12x18
63,0	3UI 270/150	3PUK23 240-270	490	709	450	350	682	12x18
80,0	3UI 370/140	3PUK 300-370	1000	883	960	290	797	12x18
100,0	3UI 370/180	3PUK 300-370	1000	883	960	290	797	12x18

